Be Certain with Belden



PROFINET Double-Ended Cord Sets

Cat5e, High-Flex, High Noise, 22 AWG, PUR Halogen-Free Jacket

Туре	0985 342 100	0985 342 104	0985 342 500
Configuration	M12 to M12	M12 to RJ45	RJ45 to RJ45
Product description	PROFINET data cable according to type C, molded on both sides with M12 male connector, D coding, stranded/shielded with green jacket.	PROFINET data cable according type C, molded M12 male connector, D coding to RJ45 connector, stranded/shielded with green jacket.	PROFINET data cable according to type C with RJ45 to RJ45 connectors, stranded/shielded with green jacket.
Technical illustration	0.6.5 (0.57)	THE STATE OF THE S	2X 11,7 [46]
Wiring diagram	M12 Color M12 1 Yellow 1 2 White 2 3 Orange 3 4 Blue 4 Nut Shield Nut	M12 Color RJ45 1 —— Yellow —— 1 2 —— White —— 3 3 —— Orange —— 2 4 —— Blue —— 6 Nut Shield Shell	RJ45 Color RJ45 1
Face views	1 = TD+ yellow 2 = RD+ white 3 = TD- orange 4 = RD- blue	3 4	12346678
Part number Standard cable lengths	0985 342 100/M	0985 342 104/M	0985 342 500/M
	1 M/2 M/3 M/4 M/5 M/10 M/15 M/20 M	0.5 M / 1 M / 2 M / 5 M / 10 M / 15 M / 20 M / 25 M / 30 M / 40 M / 50 M	0.5 M/1 M/2 M/5 M/10 M/ 15 M/20 M/30 M

PROFINET Double-Ended Cord Sets

Cat5e, High-Flex, High Noise, 22 AWG, PUR Halogen-Free Jacket

Туре	0985 342 100	0985 342 104	0985 342 500		
Degree of protection	IP67	IP67 / IP20	IP20		
Operating temperature range	-25C to +80C				
Mechanical	-25C to +80C -20°C (-4°F) to +75°C (+167°F)				
M12					
Molded body	DIID	black			
Coupling nut	PUR, black				
Contacts	Brass, nickel plated				
Insert	Brass, gold over nickel plated PUR, self extinguishing				
RJ45	r on, sen extinguishing				
	Pro-tinned coner allow				
Housing	Pre-tinned copper alloy Clear polycarbonate				
Insert					
Contacts		50 μ" gold in contact a	rea over nickel plating		
Electrical	40	4	- 4		
Current rating	4A	1.:			
Voltage rating	250V	30VAC/	42VUU		
Performance		Cat5e			
Cable specifications					
Cable jacket	PUR, halogen-free				
Color	Green				
Overall diameter	6.2mm, nominal				
Conductor	22 AWG, 7 stranded bare copper				
Insulation	Polyethylene foam skin				
Foil shield	Aluminum/polyester tape, 100% coverage				
Braid shield		Tinned copper, 85% coverage			
Agency approval	AWM 20236				
Cable type	High Flex, High Noise, PROFINET cable				
Characteristics					
		NOTE: Vibration & Oil Resistant			
		applies to M12 side only.			

The application of these products in harsh environments should always be checked before use. Specifications subject to alteration.